

6/8mm Thick Rockpanel  
Rockclad Durable.

EPDM Gasket.

Vertically fixed timber  
batten. Minimum  
thickness of 28mm

Breathable membrane.

Insulation board.

Panels fixed with Torx  
headed screws in  
accordance with  
Rockpanel specification.

Horizontally laid  
timber batten.

Sheathing Ply.

28

\* FOR ROCKPANEL SYSTEMS  
REQUIRING NHBC APPROVAL  
A CAVITY DEPTH OF 35mm IS  
REQUIRED.

THE DETAIL GIVEN BELOW OFFERS  
A GUIDE IN PRINCIPLE ONLY AND  
SHOULD BE CHECKED WITH THE  
MANUFACTURERS OF THE  
RELEVANT COMPONENT FOR  
ACCURACY BEFORE INSTALLATION

Clearance by application of  
Pre fabricated elements.

Plasterboard with internal  
paint finish.

Vertically fixed  
Timber battens.

Polythene Vapour  
Control Layer.

Timber stud wall construction  
infilled with insulation.

## DETAIL 5 - ROCKCLAD DURABLE VERTICAL SECTION TIMBER SUBSTRUCTURE TO STRUCTURAL CONCRETE WITH TIMBER STUD FRAME.

**Rockpanel**<sup>®</sup>  
a **ROCKWOOL** company



BREEAM is a registered trademark of BRE (the Building Research Establishment Ltd. Community Trade Mark E5778551).  
The BREEAM marks, logos and symbols are the Copyright of BRE and are reproduced by permission.

Green Guide Element numbers A+ rated: 1006260002 / 1006270005 / 1006280007 / 1006210008 / 1006260010 / 1006270013 / 1006280015 / 1006210016

Green Guide Element numbers with A rated: 1006230001 / 1006260003 / 1006240004 / 1006250006 / 1006230009 / 1006260011 / 1006240012 / 1006250014