

6/8mm Thick Rockpanel
Rockclad Durable.

EPDM Gasket.

Vertically fixed timber
batten. Minimum
thickness of 28mm

Breathable membrane.

Insulation board.

Panels fixed with Torx
headed screws in
accordance with
Rockpanel specification.

Horizontally laid
timber batten.

28*

* FOR ROCKPANEL SYSTEMS
REQUIRING NHBC APPROVAL
A CAVITY DEPTH OF 35mm IS
REQUIRED.

THE DETAIL GIVEN BELOW OFFERS
A GUIDE IN PRINCIPLE ONLY AND
SHOULD BE CHECKED WITH THE
MANUFACTURERS OF THE
RELEVANT COMPONENT FOR
ACCURACY BEFORE INSTALLATION

Horizontally laid
Timber battens.

Plasterboard with internal
paint finish.

Vertically fixed
Timber battens.

Medium dense solid blockwork.

DETAIL 6 - ROCKCLAD DURABLE VERTICAL SECTION TIMBER SUBSTRUCTURE TO STRUCTURAL STEEL WITH MEDIUM DENSE BLOCKWORK.

Rockpanel[®]
a **ROCKWOOL** company



BREEAM is a registered trademark of BRE (the Building Research Establishment Ltd. Community Trade Mark E5778551).

The BREEAM marks, logos and symbols are the Copyright of BRE and are reproduced by permission.

Green Guide Element numbers A+ rated: 1006260002 / 1006270005 / 1006280007 / 1006210008 / 1006260010 / 1006270013 / 1006280015 / 1006210016

Green Guide Element numbers with A rated: 1006230001 / 1006260003 / 1006240004 / 1006250006 / 1006230009 / 1006260011 / 1006240012 / 1006250014